




# RCDM+RBA Compact LED multifunction beacon with audible base

- 110 mm Ø large compact modular LED multi-functional beacon
- milky lens provides nice, homogenous light
- steady/flashing and 4 strobe light modes
- audible base with 32-tone sounder
- >95 dB sound pressure, 3 tones externally controllable
- unique, appealing product design
- high protection class IP66 & impact resistance IK08
- metal bracket for mounting on walls (accessory)
- milky-white lens for all colours
- especially suitable for construction work and general applications



## TECHNICAL DATA

Size	110 mm
Housing	Polycarbonate
Lens	Polycarbonate, smooth (milky-white), amber, red, clear, blue, green or yellow
Type of mounting	Any, conduit mounting
Cable entry	Cables are inserted from below
Connection technology	Screw terminal
Leakage current	3mA
Beacon type	Multifunction beacon

Light source	LED (1x12/2+ LEDs, depends on colour)
Duty cycle	100 %
Service life	Light source > 50.000 h
Operating temperature	-30 / +60°C
Degree of protection	IP66, UL Type 4,4X, 13
Impact resistance	IK08
Volume	Up to 95 dB
Tone	32 tones, 3 tones can be switched externally



# RCDM+RBA

## ORDER DATA

Type	24-48VAC/DC	110-240VAC	Lens colour	Nominal voltage	Voltage range (V)	Nominal current	
RCDM	850561408		amber	24-48VAC/DC	+/-10%	370 mA	
	850562408		red	24-48VAC/DC	+/-10%	370 mA	
	850564408		clear	24-48VAC/DC	+/-10%	370 mA	
	850565408		blue	24-48VAC/DC	+/-10%	370 mA	
	850566408		green	24-48VAC/DC	+/-10%	370 mA	
	850567408		yellow	24-48VAC/DC	+/-10%	370 mA	
		850561313		amber	110/120/230/240VAC	+/-10%	90 mA
		850562313		red	110/120/230/240VAC	+/-10%	90 mA
		850564313		clear	110/120/230/240VAC	+/-10%	90 mA
		850565313		blue	110/120/230/240VAC	+/-10%	90 mA
		850566313		green	110/120/230/240VAC	+/-10%	90 mA
		850567313		yellow	110/120/230/240VAC	+/-10%	90 mA

Type	Type of product	24-48 V AC/DC	110-240 V AC	Voltage range (V)	Nominal current	Mains frequency
RBA	Audible base for R series beacons	850535408		+/-10%	230mA	50-60 Hz
			850535313	+/-10%	70mA	50-60 Hz



RWA

## ACCESSORIES

Type	Type of accessory	Order number
RWA	Metal bracket for audible bases	850531900