

ASS-P, ADS-P

Tone selection
Sélection du son
Tonauswahl
Selezione tono
Selecção de tom
Selección de tono

Type
ASS-P, ADS-P



Loudness depending on frequency
Puissance sonore selon la fréquence
Lautstärke in Abhängigkeit von der Frequenz
Volume in funzione della frequenza
Volume (sonoridade) dependente da frequência
Volumen en base a la frecuencia

Variation +2dB, -3dB
Tolérance
Variation
variazioni
Variação
Variaçao
Variación

Tone table ASS-P, ADS-P

	STAGE 1 S1	Tone type	Frequency Hz	Pictogram	Repeat rate	Specific application	dB
	Tone 01	continuous	4600 Hz	— — —			103
	Tone 02	continuous	1500 Hz	— — —			99
	Tone 03	intermittent	4600 Hz	— — —	250 ms on, 250 ms off		103
	Tone 04	intermittent	1500 Hz	— — —	250 ms on, 250 ms off		99
	Tone 05	sweeping	1200 - 500 Hz	/ \ / \ / \	1 Hz	evacuation Germany DIN 33404-3	96
	Tone 06	sweeping	500 - 1200 Hz	/ \ / \ / \	rising in 3 s, 0,5 s off	Netherlands NEN 2575:2000	98
	Tone 07	alternating	800 - 1000 Hz	/ \ / \ / \	2 Hz		94
	Tone 08	sweeping	500 - 1500 Hz	/ \ / \ / \	10 Hz		94



Auer Signal